

BTC-GEN 2

BEHIND THE CAB COOLER - GENERATION 2

Compact & Heavy Duty Design!

Our Behind the Cab Cooler Kit is a compact hydraulic reservoir, filter and cooler system. The Generation 2 Behind the Cab Cooler offers an increased flow rate and larger reservoir compared to its predecessor. With a no drill quick mount frame that fits any truck chassis on the market, the heavy duty design and quality construction make this unit perfect for the most severe applications.

Typical Applications

- Fertilizer Tenders
- Conveyors (Seed & Fertilizer)
- Auger Trailers
- Propane Trailers
- Water Tankers
- Bulk Fuel Trailer
- Winch Trucks



EPG-BTCGEN2-0415



EPG
ENGINEERED PRODUCTS GROUP

2210 W. Main Ave. W Fargo, ND 58078 | 877.410.7072 | www.epgdivision.com

A DIVISION OF DAKOTA FLUID POWER, INC.



BTC-GEN 2

BEHIND THE CAB COOLER - GENERATION 2

Don't see the options you need? Contact EPG at 1(877) 410-7072

Models Available:

- EPG00160 - Electric Fan w/ Stainless Steel Chassis (304 material)
- EPG00161 - Hydraulic Fan w/ Stainless Steel Chassis (304 material)
- EPG00162 - Electric Fan w/ Carbon Steel Chassis
- EPG00163 - Hydraulic Fan w/ Carbon Steel Chassis

Standard Features:

Materials:

- Frame: #4 Finish Stainless Steel (304 material) or Powder Coated Carbon Steel
- Reservoir: 12 gallon capacity
- Cooler: High efficiency AKG Global Line Cooler w/ Hydraulic or Electric Fan - 25 PSI Bypass
- Filter: 10 Micron Cartridge Filter
- Filler Breather: 10 Micron Filler Breather w/ 4.5 PSI VAC/pressure relief and fill screen
- Porting: SAE O-Ring w/ NPT Suction Port
 - 1-1/4" O-Ring Boss Return
 - 1-1/4" O-Ring Boss Auxiliary Suction Port
 - 2" NPT Female Suction Port
- Gauge: Sight Level/Temp. Gauge

Nominal Flow Rate:

- 40 GPM (*Maximum flow rate is variable based on application. Contact Customer Service for details.*)

No Drill Quick Mount:

- Powder Coated Steel w/ vibration isolation mounts and adjustable for 33.5" to 34.5" frames

Weight:

- Approx. 207 lbs (will vary depending on options)

Dimensions:

- Approx. 34.5"W x 35"H x 10"D

Performance:

