

SEPREMIUM 125

Compressed air condensate separation

PRODUCT FEATURES

The SEPREMIUM 125 separates oil from condensate, generated by compressed air systems. The SEPREMIUM 125 uses a specially designed polypropylene filter, instead of a weir, to remove the bulk of the oil and any type of condensate drain may be applied.

The SEPREMIUM 125 covers all compressor capacities up to 125 cfm. The separation method of the SEPREMIUM 125 is based on adsorption of the oil in the condensate by the special polypropylene element. The separation process is completed by the active carbon element that removes the last bit of oil from the condensate.

- * Separation of mineral lubricants.
- * Separation of synthetic lubricants.
- * Any type of drain can be applied.



COMMERCIAL BENEFITS

- No de-rating or complicated sizing charts.
- Compact design.
- Does not incorporate a settling reservoir (no bacteria growth).
- Easy serviceable/maintenance.
- Clothing kit included.
- Test kit included.

TECHNICAL SPECIFICATIONS

Target output value	<10ppm
Maximum Oil adsorption white element	0.8 gallon
Activated carbon elements	1
Inlet connections	1/2"
Outlet connection	1/2"
Test valve	yes

Information provided herewith is believed to be accurate and reliable. However, no responsibility is assumed for its use or for any infringement of patents or rights of others, which may result from its use. In addition, JORC reserves the right to revise information without notice and without incurring any obligation.